



**Clear Solutions USA**

# ClearSol SOLV LST

---

## Technical Data Sheet

---

### **HIGH-PERFORMANCE, EXTREMELY LOW SURFACE TENSION, READILY BIODEGRADABLE SOLVENT**

#### **DESCRIPTION**

**ClearSol SOLV LST** is an extremely low surface tension, readily biodegradable & non-combustible solvent that cuts through and removes heavy greases, oils and paraffin from metal and other surfaces.\* **ClearSol SOLV LST's** high polarity and low surface tension of 19 dynes/cm provides exceptional solvency properties including fast spreading, soil penetration and removal. **ClearSol SOLV LST** is also very effective at removing bitumen from metal surfaces and is a highly attractive, environmentally-friendly alternative to conventional solvents such as p-xylene & 1,4-dimethylcyclohexane. This proven solvent technology exhibits the following attributes:

- Extremely low surface tension of 19 dynes/cm.
- Readily biodegradable.
- Non-combustible & non-DOT regulated.\*
- Fast spreading & soil penetration on metal and other surfaces.
- Excellent at removing heavy greases, oils, paraffin and bitumen.
- Eco-friendly replacement for p-xylene & 1,4-dimethylcyclohexane.

CLEAR SOLUTIONS USA  
47 North Ski Court, Gilbert, AZ 85233  
Phone: 480-631-0996

## **SPECIFICATIONS**

Appearance	Colorless liquid
Odor	Bland odor
Purity %	> 96
Molecular Weight	186 g/mol
Acid Number, mg KOH/g	0.02
Ester Number, mg KOH/g	0.44
Kb Value	43
Water, wt. %	0.01
Color, Hazen	1
Viscosity @ 20 °C	2.1 cps
Boiling Point °C	186 °C
Pour Point °C	- 42 °C
Flash Point °C	97 °C
Surface Tension, dynes/cm	19
pH (as is)	Not Applicable

## **STANDARD PACKAGING**

ClearSol SOLV LST is available in 55-gallon drums and 275-gallon totes.

## **SHELF LIFE**

ClearSol SOLV LST has a shelf life of 3 years.

\*ClearSol SOLV LST is classified as non-combustible and non-regulated by DOT in non-bulk packaging of 119 gallons or less or a net mass of 882 pounds or less per package.